

400型防震軟管(高壓軟管)-詳細規格

呼 稱 口 徑 Nominal Bore		尺 寸 Dimensions			Minimum bending radius		重量 Weight		Burst Pressure	最高使用壓力 Max. Working
		內徑 I.D.	外徑 O.D.	板厚 T	靜止狀 Static	返覆式 Repeated	裸管 Tube	Single Braid	with single wire braid	Pressure at 20
mm	inch	mm			mm		Kg/m		Kg/cm ²	Kg/cm ²
20	3/4"	20.4	30.5	0.3	80	115	0.55	0.37	220	25
25	1"	26.5	37.0	0.9	80	160	0.57	0.50	170	25
32	1-1/4"	32.0	47.0	0.3	100	170	0.77	0.63	160	20
40	1-1/2"	40.5	55.0	0.4	110	185	1.23	0.67	120	15
50	2"	53.0	71.0	0.4	120	220	2.00	0.75	120	15
65	2-1/2"	66.5	86.5	0.4	140	250	2.46	0.80	90	15
80	3"	78.0	101.0	0.4	200	270	2.92	1.10	65	10
100	4"	103.0	127.0	0.4	240	320	3.80	1.30	40	10
125	5"	128.0	154.0	0.5	350	460	5.32	1.60	45	10
150	6"	151.5	181.0	0.5	400	550	6.29	1.90	40	10
200	8"	202.5	233.5	0.6	600	850	10.21	3.20	40	10
250	10"	250.5	285.5	0.6	700	950	15.16	4.00	40	10
300	12"	300.0	337.0	0.7	900	1050	20.23	6.00	30	10
350	14"	346.6	416.6	*	1400		19.70	12.20	28	7
400	16"	396.6	466.6	*	1600		22.60	15.70	28	7
450	18"	446.6	516.6	*	3000		25.50	11.00	20	5
500	20"	497.0	577.0	*	3300		42.60	12.50	20	5
550	22"	548.0	628.0	*	3500		46.90	14.00	16	4
600	24"	599.0	679.0	*	3800		51.20	16.00	16	4

Material :SUS-304 ,SUS-316

呼 稱 口 徑 A Bore		尺 寸 Dimensions			最小彎曲半徑 Minimum bending radius		破壞壓力 Burst Pressure	壓力 Max. Working
		內徑 I.D.	外徑 O.D.	板厚 T	靜止狀 Static	返覆式 Repeated	single wire	Pressure at 20
mm	inch	mm			mm		Kg/cm ²	Kg/cm ²
8A	1/4"	8.3	11.9	0.2	25	80	280	20
10A	3/8"	10.2	14.7	0.25	25	80	250	15
15A	1/2"	13.0	18.3	0.25	30	90	200	15
20A	3/4"	19.6	25.8	0.25	35	120	150	15
25A	1"	24.9	32.1	0.25	45	130	150	15
32A	1-1/4"	32.9	40.7	0.25	50	160	100	15
40A	1-1/2"	38.2	47.8	0.3	85	170	70	10
50A	2"	50.0	60.7	0.3	120	220	60	10
65A	2-1/2"	65.0	76.0	0.3	150	330	40	10
80A	3"	78.9	90.7	0.4	200	490	35	10
100A	4"	102.5	115.5	0.4	280	750	30	10